







POSITIVE INPUT SINGLE-FLOW CMV



SELECTION GUIDE

	PUREVENT	URBAN	CUBE	LOFTY	WALLY	CAVE
						
TREATMENT	Air quality and humidity			Humidity		
MARKET	New build and renovation		Renovation			
INSTALLATION	Attic	Living space	Attic	Attic	Living space	Cellar
MAX. RECOMMENDED SURFACE	300 m ²	100 m ²	140 m ²	120 m ²	70 m ²	140 m ²
MAX FLOW	350 m ³ /h	201 m ³ /h	200 m ³ /h	176 m ³ /h	108 m ³ /h	210 m ³ /h
FILTRATION INCLUDED (other options available)	Fine particles F7 – ePM1 55%			Pollen G4 – ePM10		Pollen G4 – Coarse 65%
CONTROL	Humidity sensitive + CO ₂ option			Adjustable airflow + control based on attic temperature	Adjustable airflow + control according to supply temperature	Adjustable fixed flow rate
PREHEATING	YES 9 temperatures available from 12 to 20°C			YES 16 possible temperatures from 5 to 20°C		NO
ENERGY COUPLING	YES air/water and air/air	NO	YES air/air	NO		
COMMISSIONING	Via the VMI+ mobile application			Via a menu integrated into the housing		Via a potentiometer built into the housing
	P. 10	P. 22	P. 24	P. 28	P. 30	P. 27